

PRECEDENCE TO BE TAKEN IN HANDLING AND STORAGE: ALWAYS STORE UNUSED PORTION IN ORIGINAL CONTAINER WITH CAP SECURE. NEVER STORE IN UNLABELED OR IMPROPERLY LABELED CONTAINER. CONTENTS UNDER PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120 DEG. F. AVOID CONTACT WITH EYES.

OTHER PRECAUTIONS: AS WITH ALL CHEMICALS, USE WITH DUE CARE ACCORDING TO LABEL INSTRUCTIONS AND PRECAUTIONS. READ ENTIRE LABEL BEFORE USING. KEEP OUT OF REACH OF CHILDREN. FOR COMMERCIAL/INDUSTRIAL USE ONLY.

SECTION IX: SPECIAL PRECAUTIONS

RESPIRATORY PROTECTION (SPECIFY TYPE): NONE NORMALLY REQUIRED.
VENTILATION: LOCAL EXHAUST: NONE NORMALLY REQUIRED. MECHANICAL (GENERAL): MAINTAIN ADEQUATE VENTILATION.
PROTECTIVE GLOVES: NONE NORMALLY REQUIRED.
EYE PROTECTION: CHEMICAL SPLASH PROOF GOGGLES.
OTHER PROTECTIVE EQUIPMENT: NONE NORMALLY REQUIRED.

SECTION VIII: SPECIAL PROTECTION INFORMATION

WASTE DISPOSAL METHOD: DO NOT PUNCTURE OR INCINERATE CONTAINERS. GIVE TO A DISPOSAL SERVICE EQUIPPED TO SAFELY HANDLE AND DISPOSE OF PRESSURIZED CONTAINERS. FOLLOW LOCAL, STATE AND FEDERAL REGULATIONS FOR DISPOSAL.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE SOURCES OF FLAMES, SPARK OR HEAT. PROVIDE ADEQUATE VENTILATION. Wipe up spills. THEN RINSE WITH WATER.

SECTION VII: SPILL OR LEAK PROCEDURES

STABILITY: UNSTABLE
CONDITIONS TO AVOID: HEAT ABOVE 130 DEG. F.
INCOMPATIBILITY: NONE
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON AND NITROGEN FORMED UPON COMBUSTION. AMMONIA WILL BE RELEASED FROM CAN.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR. CONDITIONS TO AVOID: NONE

SECTION VI: REACTIVITY DATA

EMERGENCY & FIRST AID PROCEDURES: SKIN: IN CASE OF CONTACT FLUSH WITH PLENTY OF WATER. CALL A PHYSICIAN IF IRRITATION PERSISTS. EYES: IN CASE OF CONTACT FLUSH WITH PLENTY OF WATER. CALL A PHYSICIAN IF IRRITATION PERSISTS. GET MEDICAL ATTENTION.
CARCINOGENICITY: NONE KNOWN.
PRIMARY ROUTES OF EXPOSURE: INHALATION, SKIN

SECTION V: HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 25 PPM (2-BUTOXYETHANOL)
EFFECTS OF OVEREXPOSURE: SKIN: MAY CAUSE MILD IRRITATION. EYES: MAY CAUSE IRRITATION. INGESTION: MAY BE HARMFUL IF INGESTED. INHALATION: MAY BE HARMFUL IF INHALED.

MATERIAL SAFETY DATA SHEET

U. S. DEPARTMENT OF LABOR

COMPLIES WITH USDL SAFETY AND HEALTH REGULATIONS, (29 CFR 1910.1200)

IMPORTANT! THIS IS YOUR ONLY COPY. PLEASE DISTRIBUTE TO ALL PLANT LOCATIONS

CODE #: 5363

REV: 001

DATE SENT: 10/05/06

SECTION I: PRODUCT DESCRIPTION: NO. 5363 BOARDWALK (CHALKBD CL

SHELBY COUNTY PUBLIC
SCHOOLS/SNOWHILL WHS
532 BURKS BRANCH RD
SHELBYVILLE, KY 40065

MANUFACTURER:
HILL MFG CO., INC.
1500 JONESBORO ROAD
ATLANTA, GA 30315
EMERGENCY (800) 535-5053
M-F: 9-5 (404) 522-8364
PREPARED BY: RICK GLISSON
DATE PREPARED: 09/25/00

SECTION II:

HAZARDOUS INGREDIENTS:	CAS #:	%:	TLV	SARA III, #313
1) 2-PROPANOL	67-63-0	>1	400 PPM	
2) AMMONIUM HYDROXIDE	1336-21-6	>1	50 PPM	
3) 2-BUTOXYETHANOL	111-76-2	>1	25 PPM	*
4) PROPANE	74-98-6	>1	1000 PPM (OSHA)	
5) BUTANE	106-97-8	>1	800 PPM	

SECTION III: PHYSICAL DATA

BOILING POINT (DEG. F.): NOT ESTABLISHED
VAPOR PRESSURE (PSI): 46
VAPOR DENSITY (AIR=1): NOT ESTABLISHED
SOLUBILITY IN WATER: COMPLETE
SPECIFIC GRAVITY (WATER=1): 0.98
VOLITILE ORGANIC CONTENT: <25% (WT)
EVAPORATION RATE (BUT. ACE.=1): SLOWER
APPEARANCE AND ODOR: CLEAR THIN LIQUID WITH A MINT ODOR.
PH: 10.2

SECTION IV: FIRE AND EXPLOSION DATA

FLAMMABILITY: NOT FLAMMABLE AS PER FLAME EXTENSION TEST
FLAMMABLE LIMITS: LEL: NOT EST. UEL: NOT EST.
EXTINGUISHING MEDIA: WATER, CARBON DIOXIDE
SPECIAL FIRE FIGHTING PROCEDURES: KEEP CONTAINERS COOL. USE SHIELDING TO
PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING CONTAINERS.
UNUSUAL FIRE AND EXPLOSION HAZARDS: AT ELEVATED TEMPERATURES (OVER 130 DEG.
F.) CONTAINERS MAY VENT, RUPTURE OR BURST.
TRANSPORTATION: DOT HAZARD CLASSIFICATION: ORM-D